


Science Planning and Production Scenario Jolyon Martin


27 September 1995

Scenario Characterization



- End-to-End Presentation and Ops Concept
 - Integrated View of System Components
 - Demonstration of Proposed Design
 - Illustration of Operations Control

End-to-End Scenario



- **0.** Load Resource Descriptions
- 1. Capture PGE Profile
- 2. Set Up Subscriptions
- 3. Describe Production Goals Through Production Requests
- 4. Resource Planning to define non-production events
- 5. Candidate Plan Generation
 - Planning Algorithm
- 6. Activate Production Schedule
 - Feedback from Processing
- 7. Coordinate Production from Data Arrival
- 8. PGE Execution


[420-TP-007-001 4.3.5]

0. Load Resource Descriptions



- MSS Resource Configuration Information used to Initialize PDPS Database for Planning Workbench
- Resources Defined for whole DAAC
 - Strings
 - Computers
 - Disks
 - Networks
 - Services
- Planning Workbench Builds Resources Model from Defined Resources
- Allocation Scheme Depends on Resource Type

1. Capture PGE Profiles




Occurs in AITTL (PGE Profile Editor)

PGE Profile describes the data needed by the Planning Subsystem

- PGE Info
- Input Data Types and "requirement"
- Output Data Types and "yield"
- Resource Requirements
- Performance Statistics
- User Parameters

Planning

- Provides APIs to AITTL for DB storage of Profile
- Supports TRMM Activation Rules at Release A
- Uses Modeling data from AHWGP





PGE Profile Objects

PGE Profile Objects Capture . . .


- PGE Information
- PGE Dependencies Inputs & Outputs
- Information about Inputs & Outputs


PGE Profile Objects






2. Set Up Subscriptions






- Subscriptions support the Data Driven aspects of ECS production
- Planning Subscription Editor Application is mainly re-use of Advertising / Data Server services
- Update to Data Type information part of PGE Profile


3. Entry of Production Requests







- Production Requests specify
 - routine production of data over extended periods
 - or activation of PGE over extended periods
- Production Request "exploded" into many Data Processing Requests
- Translation of "template type" profile information to "specific instance" DPR information
- Grouping of multiple requests in later release
- Editor provides capabilities to Review / Modify Data Processing Requests

Exploding Production Requests









DPR Objects

DPR Objects

- Capture Information about Individual Processing Requests
- Identify Specific Granules Being Produced
- Mirror the PGE Profile Objects


DPR Objects






[420-TP-007-001 4.3.4]

4. Ground Event Resource Reservation






Resource Planner enters predictable ground events against ECS resources Ground Events specify


- Event Type / Name
- Resource Requirements
- Planning Window
- Duration


Ground Event Resource Timeline



		l	I	l	I	I	I	l		I	l i	l	[l	I
	<u> </u>		!		<u> </u>	!	<u> </u>								ļ
CPU1															
DISK1															
CPU2								SSI&	zT						
DISK2								SSI&	:T						
CERES_DSERV										MA	INT				

5. Generating Candidate Plans





"What If / Candidate Planning" - based on priorities, preferences


Predicts execution times for data processing requests and ground events
GUI & Report Statistics summarize plans for OPS

Plane are evellable for external view via decument data convert.

Plans are available for external view via document data server

Select Production Requests





Lists of Production Request define the DPRs to be planned


Planning: Algorithm Goals



The Planning Algorithm will account for

- The allocation of resources to ground events
- Dependencies between DPRs
- Resource Allocation to DPRs
- Prioritization of Data Processing Requests
- Efficiency of Production
 - scheduling tasks sharing data close together


The Plan should accurately reflect the sequence and duration of the activities which will occur within the Data Processing Subsystem as "coordinated" by the Job Scheduler COTS




Sort Algorithm

- Sort DPRs into dependant chains to order chains of tasks where ouput data from one DPR is used as input to another.
- Release A algorithm based on data arrival times supports routine production for TRMM data sets
- Additional algorithms may be defined for other instruments and processing scenarios.






Routine Production Scenario





Resource Allocation Description



- When more than one DPR at same time take the highest priority from the ordered list.
- Determine the set of computers on which the DPR may be scheduled; iterate over these
- Use the earliest start time for the DPR (latest data availability time) to find out when the computer is first available after that time. Advance time if required services not available.
- Trial allocation of DPR to computer, computer capable of "shifting" ground event within the window.
- Calculate the "cost" for data staging to that computer
 - cost based on "data transfer" vs. "time of data on disk" to determine relative effectiveness of the trial allocation in view of possible ground events
 - precise formula TBD. clearly a function of file size
 - goal is to allocate chains of PGEs to the same resource
- Allocate to the cheapest resource. DPR allocated to CPU. Files allocated to Disk.
- Update output file predicted times
- Uses same first come first served priority CPU allocation as AutoSys
- Uses same first in first out disk allocation as Data Processing









[420-TP-007-001 4.3.4]


6. Activating a Plan






[305-CD-010-001 4.3.7]

7. Coordinating Production





Subscription Manager manages ECS Data Dependencies and converts to AutoSys Job Dependencies


Checks Quality Thresholds for input data


Uses CSS guaranteed asynchronous message passing

305-CD-011-001 Section 4


8. PGE Execution

(Data Processing)







Agenda



- Introduction
- Planning and Data Processing Subsystem (PDPS) Overview
- Science Planning and Production Scenarios
- Planning Workbench Design
 - Planning Workbench Implementation Plan

Workbench Context









Workbench Architecture


Timeline Customization (C++) Workbench **Timeline GUI User Interface** (Builder Xcessory) (Delphi/HCL) MOTIF **MOTIF Workbench Customization (C++) Application Planning Classes Resource Classes Scheduling Classes** (Delphi/HCL) (Delphi/HCL) (Delphi/HCL) **Database Interface (Rogue Wave)** Services MSS/CSS Services **PDPS Database (Sybase)**


Workbench Processes






Workbench High Level Model






Agenda



- Introduction
- Planning and Data Processing Subsystem (PDPS) Overview
- Science Planning and Production Scenarios
- Planning Workbench Design



Planning Workbench Implementation



Planning Workbench Sizing


- Sizing Estimates
 - Custom Code: 5500 SLOC (18000 for Planning Subsystem)
 - Delphi re-use: 2000 SLOC equivalent application code
 + GUI re-use
- This is the CDR Baseline (NO CHANGE)

Planning Workbench Implementation Schedule



- Three-phase Implementation for Release A
 - Phase 1 Ends December 1995
 - Phase 2 Ends March 1996
 - Phase 3 Ends June 1996
- Allocation of Planning Workbench To Implementation Phases
 - GUI Development Phase 1
 - Early Development of the Planning Algorithm Phase 1
 - Code and Test Phase 2 and 3





For the "best laid plans" . . .

THE PLANNING WORKBENCH

